Winshuttle, FM v20.2.8

Server-Side Installation -(Importing transports to Winshuttle Function Module)

Version 1.0 March, 2022

Pre-requisite:

Please ensure that you have completed steps of document

"1Server Side Installation & Upgrade Instructions - WFM v20.2.8"

Procedure

The transport import is a standard procedure and will come as two files (K900nnn.XXX and R900nnn.XXX); where nnn will be a SAP generated number and 'XXX' will be respective SAP system ID (SID) for relevant server.

1. Goto DIR_TRANS path (e.g. /usr/sap/trans on Windows NT) (e.g. \usr\sap\trans on unix) and copy the files into the subdirectories "cofiles" and "data" as shown below:

The K_ file is to be copied into "cofiles" directory and R_file is to be copied into the "data" directory

- 2. Logon into SAPGUI and start transaction **STMS** and select the import queue for the target system
- 3. Go to menu option **Others>Extras> Other Requests> Add**, enter request XXXK900nnn
- 4. Select the request number XXXK900nnn
- 5. Go to Menu option **Request > Import**, to Import the XXXK900nnn into the system.
- 6. In case your target client is not 000, then ensure to select the Option "Ignore Non-Permitted Table Class".
- 7. For Basis release higher than 700, ensure to select the option 'Ignore Invalid Component Version'

Date Execution Options	
Import Options	
✓ Leave Transport Request in Queue for Later Import	
Import Transport Request Again	
Overwrite Objects in Unconfirmed Repairs	
Ignore invalid transport type	
Ignore invalid table class	
Skip predecessor relationships	
Ignore Invalid Component Version	
	2 ×